

DEUREX® T 1501 W

TECHNICAL INFORMATION

Chemical description: Water-based emulsion of paraffin wax

Applications: - Raw material for water-based

Coatings, paintings and printing inks

Concrete admixture

Properties: - Excellent water repellency and waterproofing on wood, paper, textile

Very good blocking resistanceImproved UV & ozone protection

- Increased surface slip

- Increased scratch and abrasion resistance

- Good anti-graffiti properties

Processing: - Stir well before usage, consume quickly after opening

Storage, shelf life: - Store at temperatures between +5 °C and +28 °C, Avoid frost

- Shelf life 6 month in closed original container

Technical data: Colour: White

Solid: Paraffin wax Form of delivery: Liquid Packaging: IBC 1,000 kg

Minimum Maximum Method Drop point (solid): 47 °C 55 °C LV 12 (DGF M-III 3) Solid content*: 49 % 51 % Emulsifier system: anionic/nonionic 10.0 pH-value*: 8.0

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.

© - registered trademark by DEUREX

Revision:

^{*} part of certificate of analysis