

DEUREX® E 0912 O

TECHNICAL INFORMATION

Chemical description: Oil-based wax dispersion, Polyethylene wax, based on DEUREX® E 09

Benefits: Excellent abrasion and scratch resistance

Application: Oil-based Printing inks
Offset printing inks (Sheetfed, Web offset, Heatset, Coldset)

Properties:

- Excellent abrasion- and scratch resistance
- Excellent gloss retention and rub resistance
- Very good slip (low COF) and anti-blocking
- Improved chemical and temperature resistance
- Improved transparency and good overprintability
- 100% non-volatile and fast-setting

Based on: Linseed oil (Can be made with any other oil)

Technical data:

Colour:	White opaque
Delivery form:	Liquid
Packaging:	IBC 950 kg, Drum 190 kg

	Minimum	Maximum	Method
Drop point (wax):	110 °C	120 °C	LV 12 DGF M-III 3
Typical value:		98 % < 12 µm	LV 09
Particle size:		50 % ~ 6 µm	DIN EN ISO 1524
Solid content*:	34 %	36 %	LV 6 DIN EN ISO 787-2

* part of certificate of analysis

Processing:

- Stir well before usage
- Consume quickly after opening

Storage, shelf life:

- Store at temperatures between +5 °C and +28 °C, avoid frost
- Shelf life 6 months in closed original container

Alternative delivery forms:

DEUREX® E 09 K – Fine granules
 DEUREX® E 0908 W – Water-based dispersion, 98% < 8 µm
 DEUREX® E 0915 M – Micronized powder, 98% < 15 µm
 DEUREX® E 0920 M – Micronized powder, 98% < 20 µm
 DEUREX® E 0925 M – Micronized powder, 98% < 25 µm

Alternative products: BIOMER® – biodegradable waxes