

## DEUREX E 09 K

### TECHNICAL INFORMATION

- Chemical description:** Non polar hard Polyethylene wax
- Applications:** Masterbatch  
Powder coatings  
Hot melts  
Raw materials for micronized waxes
- Properties:**
- Modification of viscosity
  - Good dispersing properties
  - Increased colour yield
- Benefits:**
- Very narrow C-chain distribution
  - Crystalline and easy to grind
  - Very hard PE wax, good surface protection
  - Can partly substitute classic Fischer-Tropsch waxes

**Technical data:**

Colour: White  
Delivery forms: **DEUREX E 09 K** = Fine granules

	Minimum	Maximum	Method
Drop point*:	104 °C	118 °C	ASTM D 3954
Acid value:		0 mgKOH/g	ASTM D 1386
Viscosity (140 °C)*:		40 mPas	ISO 3219
Penetration:	3 mm*10 <sup>-1</sup>	6 mm*10 <sup>-1</sup>	ASTM D 1321
Density (23 °C):	0.94 g/cm <sup>3</sup>	0.96 g/cm <sup>3</sup>	ISO 1183

\* Part of certificate of analysis

**Approvals:** Food contact approvals

**Alternative products:** See <https://www.deurex.com/productsearch/DEUREX-E-09-K/>

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.