

DEUREX A 2015 M

TECHNICAL INFORMATION

Chemical description:	Bio-based micronized Ethylene-Bis-Steramid wax (EBS)			
Benefits:	<ul style="list-style-type: none">- Very high temperature stability (no yellowing)- Guaranteed maximum particle size and constant and narrow particle size distribution			
Applications:	<u>Paints and coatings</u> <ul style="list-style-type: none">- Powder coatings- Industry- and wood coatings <u>Masterbatch</u>			
Properties:	<ul style="list-style-type: none">- Good grindability- No gloss reduction- Degassing agent- Good anti-blocking and slip			
Technical data:	Colour:	White		
	Delivery form:	DEUREX A 2015 M = Micronized powder		
		Minimum	Maximum	Method
	Particle size*:		98 % < 15 µm	ISO 13320
	Typical value:		50 % ~ 6 µm	
	Drop point*:	142 °C	151 °C	ASTM D 3954
	Penetration:	2 mm*10 ⁻¹	5 mm*10 ⁻¹	ASTM D 1321
	Density (23 °C):	0.98 g/cm ³	1.00 g/cm ³	ISO 1183
	* Part of certificate of analysis			
Approvals:	Food contact approvals			
Alternative products:	See https://www.deurex.com/productsearch/DEUREX-A-2015-M/			

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.