

## DEUREX A 27 P

### TECHNICAL INFORMATION

**Chemical description:** Vegetable Oleamide wax

**Application:** Plastics industry (e.g. PVC, PE and PP)

Paper industry

- Defoamer for the production of paper
- Good overprintability and wet printing properties

Metal processing

- Surface lubricant for metal production

Printing inks

- Improves the dye distribution

Rubber industry

- Reduction of the tacks in CSM roller mixer
- Mold release agents
- Increases the abrasion resistance
- Reduction of sulphurization

**Properties:** - Excellent slip

- Lubricant
- Release agent
- Very good Anti-blocking properties
- Processing aid
- Abrasion resistance
- Dust free

**Technical Data:**

Colour: Light yellow  
Consistencies: **DEUREX A 27 P** = Powder

	Minimum	Maximum	Method
Drop point*:	70 °C	80 °C	ASTM D 3954
Acid value*:		1 mg KOH/g	ASTM D 1386
Viscosity (140 °C)*:		10 mPas	ISO 3219
Penetration:		65 mm*10 <sup>-1</sup>	ASTM D 1321
Density (23 °C):	0.91 g/cm <sup>3</sup>	0.92 g/cm <sup>3</sup>	ISO 1183

\* Part of certificate of analysis

**Approvals:** Food contact approvals

**Alternative products:** See <https://www.deurex.com/productsearch/DEUREX-A-27-P/>

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.