

DEUREX® A 27

TECHNICAL INFORMATION

- Chemical description:** Oleamide wax
- Application:**
- Plastics industry (e.g. PVC, PE and PP)
 - Rubber industry
 - Paper industry
 - Metal processing
 - Printing inks
- Properties:**
- Good antiblocking
 - Excellent slip
 - Defoamer for the production of paper
 - Lubricant
 - Release agent

Technical Data: Colour: Light yellow
Consistencies: **DEUREX A 27 P** = Powder

	Minimum	Maximum	Method
Drop point*:	70 °C	79 °C	LV 12 (DGF M-III 3)
Acid value*:		1 mg KOH/g	DIN EN ISO 2114
Viscosity (140 °C):	6 mPas	11 mPas	LV 2 (DIN EN ISO3104)
Penetration:	2.0 mm*10 ⁻¹	5.0 mm*10 ⁻¹	LV 4 (DIN 51579)
Density (23 °C):	0.91 g/cm ³	0.92 g/cm ³	LV 3 (DIN EN ISO 1183)

* Part of certificate of analysis

Approvals: DEUREX A 27 is approved for use in the production of consumer good used for food contact.
EU: Regulation (EU) 10/2011 dated 14. January 2011 – Ref.-No.:68960
USA: FDA 21 CFR §§ 177.1350, 178.3910, 179.45, 181.28
Approvals with regard to limitations and migration values in the end use application

Safety: The product is no dangerous preparation according to Directive 1999/45/EC. It is not subject to labelling according to EC Directive 67/548/EEC and Regulation (EC) 1272/2008.