

DEUREX E 08

TECHNICAL INFORMATION

Chemical description: Non polar Polyethylene wax


Applications:

- Carrier for pigment concentrates
- Plastics industry
- Modification of adhesives and hot melt coatings
- Printing inks
- Paints and coatings
- Care products
- Additive for hydrocarbon waxes

Properties:

- Dispersing agent
- Excellent lubricant
- Good matting
- Good abrasion

Technical data:



Colour:	White		
Delivery form:	DEUREX E 08	= Fine granules	
	Minimum	Maximum	Method
Drop point*:	112 °C	120 °C	DGF M III 3
Acid value:		0 mg KOH/g	DGF M IV 2
Viscosity (140°C)*:	400 mPas	600 mPas	DGF M III 8
Penetration:		1.0 mm*10 ⁻¹	DGF M III 9b
Density (23°C)	0.93 g/cm ³	0.94 g/cm ³	ISO 1183

* part of certificate of analysis

Approvals: Food contact approvals

Alternative products: See <https://www.deurex.com/productsearch/DEUREX-E-08/>

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.