

DEUREX EV 03

TECHNICAL INFORMATION

Chemical description: Copolymere Ethylene Vinylacetate wax (EVA-wax)

Applications:

- Paints and coatings, e.g. 2 layer-metallic-automotive coatings
- Polar pigment concentrates
- Plastics industry
- Masterbatch

Properties:

- Thixotropic agent
- Anti-settling agent
- Dispersing agent

Technical data:



	Minimum	Maximum	Method
Drop point*:	96 °C	104 °C	DGF M III 3
Vinyl Acetate content:	10 %	14 %	FTIR
Acid value*:		0 mg KOH/g	DGF M IV 2
Viscosity (140°C)*:	200 mPas	600 mPas	DGF M III 8
Penetration:		7.0 mm*10 ⁻¹	DGF M III 9b
Density (23°C)	0,93 g/cm ³	0,95 g/cm ³	ISO 1183

* part of certificate of analysis

Approvals: Food contact approvals

Alternative products: See <https://www.deurex.com/productsearch/DEUREX-EV-03/>

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.