

DEUREX T 3908 W

TECHNICAL INFORMATION

Chemical description: Water-based dispersion based on modified Fischer-Tropsch wax DEUREX T 39

Benefits:

- Excellent abrasion and scratch resistance

Application:

- Water-based coatings and water-based printing inks
- Water-based lubricant and release agent
- Hotmelts

Properties:

- Improved slip
- Improved chemical and temperature resistance
- Improved transparency and good overprintability
- Very good anti-blocking properties
- Underwater granulation
- Direct granule treatment
- Non-classified dispersion (GHS/CLP)

Solid content: Modified Fischer-Tropsch wax

Solvent: Water

Technical data:

Colour:	White opaque
Delivery form:	Liquid
Packaging:	IBC 950 kg, drum 200 kg, canister 10 kg

	Minimum	Maximum	Method
Drop point (wax):	110 °C	120 °C	ASTM D 3954
Solid content*:	44 %	46 %	IR Moisture-Analyzer
Particle size*:		98 % < 8 µm	ISO 1524
Typical value:		50 % ~ 3 µm	
Emulsifier system:	non-ionic		
pH value:	6.5	8.5	pH-Electrode

* part of certificate of analysis

Processing:

- Stir well before usage
- Consume quickly after opening

Storage, shelf life:

- Store at temperatures between +5 °C and +28 °C
- Avoid frost
- Shelf life 6 months in closed original container

Alternative delivery forms: See <https://www.deurex.com/productsearch/DEUREX-T-3908-W/>

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.