

DEUREX® BENZOIN

	TECHNICAL INFORMATION			
Chemical description:	Benzoin			
Applications:	Degassing agent for powder coatings			
Properties: - - - -	Effective and rapid degassing Without any yellowing (< 230 °C) Good printability of the powder coating remains Good adhesion of labels remains			
Technical data:	Colour: Delivery forms:	Off-white DEUREX® BENZOIN = Powder		
		Minimum	Maximum	Method
	Drop point*:	130 °C	137 °C	ASTM D4591
	Density (23 °C):	1.25 g/cm ³	1.35 g/cm ³	LV 3 (DIN EN ISO 1183)
	Shelf life:	12 months (In closed, original containers in compliance with storage conditions)		
	* Part of certificate of analysi	S		

Safety:

This product is not classified as dangerous preparation according to Directive 1999/45/EC. It is not subject to labelling according to EC Directive 67/548/EEC and Regulation (EC) 1272/2008.

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions. (a) - registered trademark by DEUREX