

DEUREX® FLOWRESIN

TECHNICAL INFORMATION

Chemical description: Polyacrylate - powder coating flow modifier

Benefits:

- Excellent flow
- Excellent gloss

Applications: Powder coatings

- Polyester
- Hybrid
- Epoxy
- Polyurethane
- Acrylate

Properties:

- Anti-cratering and leveling agent
- Improved flow and leveling
- Eliminate pinholes, fisheyes, craters and orange peel
- Broadens cross-compatibility between powder formulations
- No matting effect
- Minimized dusting behaviour, free-flowing powder

Technical data:

Colour: White
Delivery form: **DEUREX® FLOWRESIN** = Powder

	Minimum	Maximum	Method
Activity:	65 %	70 %	
Density (23 °C) (Polymer):	1.20 g/cm ³	1.30 g/cm ³	LV 3 (DIN ISO 1183)

* Part of certificate of analysis

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.

® - registered trademark by DEUREX