

DEUREX T 1601 W

TECHNICAL INFORMATION

Chemical description:	Water-based emulsion of paraffin wax		
Applications:	<ul style="list-style-type: none"> - Raw material for water-based coating systems <p><u>Coatings, paintings and printing inks</u></p> <p><u>Construction chemicals, concrete curing, gypsum, fiber cement</u></p>		
Properties:	<ul style="list-style-type: none"> - Improved water repellency and waterproofing - Very good blocking resistance - Improved UV & ozone protection - Increased surface slip - Increased scratch and abrasion resistance - Good anti-graffiti properties 		
Processing:	<ul style="list-style-type: none"> - Stir well before usage, consume quickly after opening 		
Storage, shelf life:	<ul style="list-style-type: none"> - Store at temperatures between +5 °C and +28 °C, Avoid frost - Shelf life 6 months in closed original container 		
Technical data:	Colour:	White	
	Solid:	Paraffin wax	
	Form of delivery:	Liquid	
	Packaging:	IBC 1,000 kg, Drum 200 kg, Canister 10 kg	
		Minimum	Maximum
	Drop point (solid):	60 °C	70 °C
	Solid content*:	44 %	46 %
	Emulsifier system:	non-ionic	
	pH-value*:	7.0	9.0
			pH-electrode
	* part of certificate of analysis		
Approvals:	Food contact approvals		
Alternative products:	See https://www.deurex.com/productsearch/DEUREX-T-1601-W/		

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.