

DEUREX TO 83 G

TECHNICAL INFORMATION

Chemical description:

Oxidized Fischer-Tropsch-wax

Benefits:

- Hard and scratch-resistant wax with a hydrophilic character

Applications:

- Production of water-based emulsions and dispersions for:
- Textile industry (improved sewability and cutting of textiles)
 - Care products (hydrophobing, gloss, hardness)
 - Water-based coatings (slip, abrasion and scratch resistance)
 - Water-based printing inks (slip, abrasion and scratch resistance)
 - Paper industry (hydrophobing, tensile strength, stability)
 - Polishes (surface improvement)
 - Leather (surface improvement, hydrophobing)
 - Anti-corrosive agent

Technical data:

Colour: Off-white
Delivery form: **DEUREX TO 83 G** = Granules

	Minimum	Maximum	Method
Drop point*:	101 °C	110 °C	ASTM D 3954
Acid value*:	25 mgKOH/g	35 mgKOH/g	ASTM D 1386
Viscosity (140 °C):		20 mPas	ISO 3219
Penetration:		4.0 mm*10 ⁻¹	ASTM D 1321
Density (23 °C):	0.94 g/cm ³	0.95 g/cm ³	ISO 1183

* Part of certificate of analysis

Alternative products:

See <https://www.deurex.com/productsearch/DEUREX-TO-83-G/>