

DEUREX P 36 TEX

TECHNICAL INFORMATION

Chemical description:	Polypropylene wax with texture effect		
Application:	<u>Paints and coatings</u> - Powder coatings, industrial coatings, decorative paints, furniture and parquet coatings <u>Printing inks</u> - Gravure inks, overprint varnishes, screen printing inks, flexo printing inks <u>Paper industry</u>		
Properties:	- Texturing agent - Reduce gloss - High melting point - Antisettling properties - Provide high stability with waterbased and solventbased systems		
Benefits:	- Constant texture and structure		
Technical data:	Color:	White	
	Delivery form:	Finest powder	
		Minimum	Maximum
	Drop point*:	150 °C	170 °C
	Acid value:	0 mgKOH/g	ASTM D 1386
	Viscosity (160 °C)*:	80 mPas	150 mPas
	Penetration:	2 mm*10 ⁻¹	ASTM D 1321
	Density (23 °C):	0.87 g/cm ³	0.89 g/cm ³
			ISO 1183
	* Part of certificate of analysis		
Approvals:	Food contact approvals		
Alternative products:	See https://www.deurex.com/productsearch/DEUREX-P-36-TEX/		

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.