

DEUREX E 18 K

TECHNICAL INFORMATION

Chemical description: Non polar, high molecular polyethylene wax

Applications:

- Masterbatch
- Plastics industry
- Hot melts
- Raw material for micronized waxes
- Raw material for emulsions
- Care products

Properties:

- Carrier for pigment concentrates
- Dispersing agent
- Good abrasion resistance
- Matting agent
- Slip agent

Technical data:

Colour: White
Delivery forms: **DEUREX E 18 K** = Fine granules

	Minimum	Maximum	Method
Drop point*:	112 °C	120 °C	ASTM D 3954
Acid value:		0 mg KOH/g	ASTM D 1386
Viscosity (140 °C)*:		250 mPas	ISO 3219
Penetration:	1 mm*10 ⁻¹	4 mm*10 ⁻¹	ASTM D 1321
Density (23 °C):	0.93 g/cm ³	0.95 g/cm ³	ISO 1183

* Part of certificate of analysis

Approvals: Food contact approvals

Alternative products: See <https://www.deurex.com/productsearch/DEUREX-E-18-K/>

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.