

DEUREX® H 85 G

TECHNICAL INFORMATION

- Chemical description:** Hybrid wax based on Sugar Cane wax and Hydrocarbon wax
- Production process:** Homogeneously melted wax hybrid
- Benefits:** Hybrid waxes offer a variety of wax properties:
- Contains renewable and compostable waxes of the type DEUREX® X 52 according to DIN EN 13432
 - Contains long-chained Hydrocarbon waxes to increase scratch, abrasion and heat resistance
- Applications:**
- Raw material for bio based products
- Partially natural product, ideal for sustainable formulations
- Care products
- Silky gloss after polishing
 - Water repellency
- Production of water based emulsions
- Emulsifiable under pressure using only a small dosage of emulsifier
- Paper, wood and textiles
- Improved slip
 - Water repellency
 - Improved sewing properties

Technical Data:

Colour: Amber
Delivery form: **DEUREX H 85 G** = Granules

	Minimum	Maximum	Method
Drop point**:	80 °C	90 °C	LV 12 (DGF M-III 3)
Acid value*:	20 mg KOH/g	30 mg KOH/g	DIN EN ISO 2114
Viscosity (140 °C):		40 mPas	LV 2 (DIN EN ISO3104)
Penetration:	3 mm*10 ⁻¹	7 mm*10 ⁻¹	LV 4 (DIN 51579)
Density (23 °C):	0.90 g/cm ³	0.93 g/cm ³	LV 3 (DIN EN ISO 1183)

* Part of certificate of analysis

Alternative delivery form: **DEUREX® H 8108 W** – Water-based emulsion, 98% < 1 µm

Alternative products: **DEUREX® H 81G** – Hybrid wax based on Sugar Cane wax and Polyethylene wax
DEUREX® X 52 G – Sugar Cane wax granules

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.
® - registered trademark by DEUREX