

## DEUREX P 36 G

### TECHNICAL INFORMATION

**Chemical description:** Non polar Polypropylene wax

**Application:**

- Plastics industry (e.g. PVC)
- High quality pigment concentrates
- Modification of hotmelts
- Printing inks
- Paints and coatings
- Masterbatch

**Properties:**

- Easy to disperse
- Lubricant
- Matting agent
- Dust free

**Benefits:**

- Very low viscosity

**Technical data:** Color: White  
Delivery form: **DEUREX P 36 G** = Granules

	Minimum	Maximum	Method
Drop point*:	150 °C	170 °C	ASTM D 3954
Viscosity (160 °C)*:	80 mPas	150 mPas	ISO 3219
Penetration:		2 mm*10 <sup>-1</sup>	ASTM D 1321
Density (23 °C):	0.87 g/cm <sup>3</sup>	0.89 g/cm <sup>3</sup>	ISO 1183

\* Part of certificate of analysis

**Approvals:** Food contact approvals

**Alternative products:** See <https://www.deurex.com/productsearch/DEUREX-P-36-G/>

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.