

DEUREX T 39 A

TECHNICAL INFORMATION

- Chemical description:** Micronized modified Fischer-Tropsch-Wax
- Applications:**
- Paints and coatings
 - Can coatings, industrial and wood coatings
 - Printing inks
 - Gravure, flexo and overprinting inks
- Properties:**
- Very hard wax
 - Excellent abrasion and scratch resistance
 - Very good chemical and weather resistance
 - Improved UV-resistance and anti-blocking properties
 - Good matting properties
- Benefits:**
- Guaranteed maximum particle size and constant and narrow particle size distribution
 - Easily dispersible without lump or coagulate formation
 - Easy to disperse without heating
- Technical data:**
- | | | | |
|------------------|------------------------------|------------------------|-------------|
| Colour: | White | | |
| Delivery form: | Finest powder, 98 % < 150 µm | | |
| | Minimum | Maximum | Method |
| Drop point* | 110 °C | 120 °C | ASTM D 3954 |
| Penetration: | | 2 mm*10 ⁻¹ | ASTM D 1321 |
| Density (23 °C): | 0.94 g/cm ³ | 0.95 g/cm ³ | ISO 1183 |
- * Part of certificate of analysis
- Approvals:** Food contact approvals
- Alternative products:** See <https://www.deurex.com/productsearch/DEUREX-T-39-A/>

This data sheet is based on our current knowledge and experience. In view of the individual factors that may affect processing and application, this data does not relieve users from the responsibility of carrying out their own tests and experiments, neither do they imply any legally binding assurance of certain properties. Existing industrial/commercial protective laws have to be considered by the recipient. Updated versions of the data sheet replace all formerly existing versions.