

DEUREX H 92 A

TECHNICAL INFORMATION

Chemical description: Hybrid wax based on Polyethylene-, Fischer-Tropsch- and Amide wax

Applications:

Paints and coatings

- Powder coatings, industrial coatings
- Furniture and parquet coatings
- Can coatings

Printing inks

- Gravure printing, overprint varnishes, screen printing inks
- Flexo-, web-fed-, sheetfed offset-, and coldset inks

Properties:

- Excellent matting properties
- Excellent sandability
- Improved abrasion and scratch resistance
- Reduction of the friction coefficient
- Improved anti-blocking properties
- Good degassing agent
- Gloss reduction properties
- Improves the flowability of powders
- Soft-feel effect in wood coatings

Technical data:

Colour: White
Delivery form: Finest powder, 98 % < 150 µm

	Minimum	Maximum	Method
Drop point*:	130 °C	140 °C	ASTM D 3954
Acid value:		5 mgKOH/g	ASTM D 1386
Penetration:		5 mm*10 ⁻¹	ASTM D 1321
Density (23 °C):	0.97 g/cm ³	0.99 g/cm ³	ISO 1183

* Part of certificate of analysis

Approvals: Food contact approvals

Alternative delivery form: See <https://www.deurex.com/productsearch/DEUREX-H-92-A/>